

0716

Hose coupling, 3/4"(Q)



3/4" hose coupling.

Technical Data

Item Number	0716
Couplings Size	3/4 "
Material	Chromium-plated brass Galvanized steel (DIN 1.09035) Synthetic rubber
Complies with FDA Regulation I CFR 21 ¹	No
Complies with REACH Regulation (EC) No. 1907/2006	Yes **
Complies with California Proposition 65	No
SCIP number	095b5bea-9314-4e2d-987b-8726dbd84c43
Complies with Halal and Kosher	Yes
PFAS, Phthalates and BPA intentionally added	No
Box Quantity	10 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	3180 Pcs.
Quantity Per Layer (Pallet)	0 Pcs.
Box Length	330 mm
Box Width	180 mm
Box Height	85 mm
Length/Depth	160 mm
Width	67 mm
Height	50 mm
Net Weight	0.13 kg
Weight cardboard (Recycling symbol "20" PAP)	0.0118 kg
Tare total	0.0118 kg
Gross Weight	0.14 kg
Cubic metre	0.000536 M3
Max. cleaning temperature (Dishwasher)	80 °C
Max usage temperature (non food contact)	70 °C
Min. usage temperature ³	-30 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	25 Bar
GTIN-13 Number	5705020007163
GTIN-14 Number (Box quantity)	15705020007160
Customs Tariff No.	74122000
Country of origin	Denmark

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.